

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1-17. (cancelled)

18. (currently amended) A warning sign comprising first and second parts pivotably interconnected at their in use upper ends and pivotable between a first storage position in which the first and second parts are arranged in side-by-side relationship and a second operative position in which the first and second parts are at an angle to one another, detent means for releasably retaining the first and second parts in the second operative position, ~~and~~ a third part releasably supportable by the detent means, and a fourth display part releasably engageable with the third part.

19. (currently amended) A warning sign as ~~claim~~ claimed in Claim 18, wherein the two parts have ground contacting foot portion at their in use lower ends, so that, with said foot portion or portions of one part spaced from said foot portion or portions of the other part, the sign will be self-supporting on the ground.

20. (currently amended) A warning sign as claimed in Claim 18, wherein the ~~detents~~ detent means comprises at least one projection and at least ~~on one~~ corresponding aperture or recess, the projection being ~~arrange~~ arranged to fit in the aperture or recess as a snap or friction ~~fir~~ fit when the first and second parts are in the second operative position.

21. (previously presented) A warning sign as claimed in Claim 20, wherein the first and second parts each have one said projection which cooperates with one said corresponding aperture or recess formed in the other part.

22. (currently amended) A warning sign as claimed in Claim 20, wherein the third part includes a support portion having one or more openings dimensioned to receive a corresponding said ~~production~~ projection therethrough.

23. (currently amended) A warning sign as ~~claim~~ claimed in Claim 22, wherein the or each opening in the third part is a through-hole.

24. (currently amended) A warning sign as claimed in Claim 22, wherein the said projection can only be inserted into the corresponding opening of the third part when the first and second ~~pare~~ parts are in the first storage position.

25. (previously presented) A warning sign as claimed in Claim 22, wherein the said projection can only be removed from the corresponding opening of the third part when the detent means is released.

26. (previously presented) A warning sign as claimed in Claim 22, wherein the or each opening in the third part is a recess formed in an edge of the third part.

27. (previously presented) A warning sign as claimed in Claim 22, wherein at least one said recess is keyhole shaped so as to be snap-fit engageable with the said projection of the detent means.

28. (currently amended) A warning sign as claimed in Claim 26, wherein the third part, in use, ~~in~~ is engageable with and disengageable from the projection of the detent means, when the first and second parts are in the first storage position and the second operative position.

29. (cancelled)

30. (currently amended) A warning sign as claimed in Claim ~~[[29]]~~ 18, wherein the third part includes an elongated

channel in which the bottom end of the fourth display part is receivable.

31. (currently amended) A warning sign as claimed in Claim ~~[[29]]~~ 18, wherein the third part comprises two members, each member including an elongate channel in which a side of the fourth display part is, at least in part, receivable.

32. (currently amended) A warning sign as claimed in Claim ~~[[29]]~~ 18, wherein the third part includes a transparent holder for holding the fourth display part.

33. (previously presented) A warning sign as claimed in Claim 32, wherein the transparent holder is a sleeve into which the fourth display part can be slidably inserted.

34. (new) A warning sign comprising first and second parts pivotably interconnected at their in use upper ends and pivotable between a first storage position in which the first and second parts are arranged in side-by-side relationship and a second operative position in which the first and second parts are at an angle to one another, detent means for releasably retaining the first and second parts in the second operative position, a third part releasably supportable by the detent means, and a fourth display part releasably engageable with the third part,

wherein the third part includes a transparent holder for holding  
the fourth display part.